SDX5

Technical Specifications

- type : 2-way hiFi Pro, sealed box
- woofer : 5,25" CP type
- tweeter : 1" mylar ferro cooled
- protection : system auto-reset 1-guard
- impedance : 8Ω
- RMS power low-imp.
  AES rated : 70 Watts
  music - program : 80 Watts
  dynamic peak : (lo-cut) 250 Watts
  SPL 1 watt / 1 m : 91dB
  SPL max peak : 115dB
- Freq range : 70 - 20000 Hz
- dispersion : 120° H x 100° V
- IP rating : 54
- enclosure material : enforced PolyPlastic
- bracket included : U-type
- dimensions (h x w x d) : 244 x 179 x 154
- weight : 2,07 Kg

The APart SDX5 2-way design cabinet loudspeaker probably is one of the most cost-effective loudspeakers for the contractor market.
The SDX5 is equipped with an auto-reset protection system.
It makes the SDX5 loudspeaker very suitable for the distribution of background music.
The loudspeaker comes standard with a U-type bracket.
The SDX5 loudspeakers can be used outdoor. However, be aware of the fact that the loudspeaker terminals are not protected and that the grill is made of plasticized painted metal.
This means direct exposure to rain or water is not recommended.
In case this is really needed, we recommend to use the APart MASK loudspeaker series.